Philips
Audio extension cable

2,5 m

2 RCA (M) - 2 RCA (F)

SWA2800W

Ensure a reliable connection

with this audio extension cable

Depend on this cable to provide you with a reliable audio connection between components.

Enjoy good audio quality
- Nickel-plated connectors for reliable contact
- High purity copper conductor for reliable signal transfer

Protects against signal loss
- Bare copper shielding

Easy installation
- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

Enjoy extended durability
- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

Audio extension cable
2,5 m 2 RCA (M) - 2 RCA (F)

SWA2800W/10

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 9.5 x 23.5 x 2.5 cm
- Nett weight: .06 kg
- Gross weight: .08 kg
- Tare weight: .02 kg

Outer Carton
- Outer carton (L x W x H): 33.9 x 26.3 x 22.8 cm
- Nett weight: 1.44 kg
- Gross weight: 2.74 kg
- Tare weight: 1.3 kg

Inner Carton
- Inner carton (L x W x H): 24.4 x 10.4 x 10.1 cm
- Nett weight: .24 kg
- Gross weight: .4 kg
- Tare weight: .16 kg

Product highlights

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

Molded plug
Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Bare copper shielding
Bare copper shielding protects against signal loss.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Nickel-plated connectors
Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Issue date 2008-08-17
Version: 1.0.5
12 NC: 8670 000 35548
EAN: 87 12581 38266 7

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com